

Claims:

1. A method for processing a JAVA class to produce an XML document, comprising:
loading the named JAVA class;
5 determining if the loaded JAVA class implements a predefined interface, said
predefined interface comprising annotations including a first parameter, for associating said
JAVA class field with a corresponding XML element tag, a second parameter, for
specifying a JAVA class to be instantiated when constructing said JAVA class field from
said XML file, a third parameter, for identifying a JAVA method to invoke for retrieving
10 said JAVA class field, and a fourth parameter, for identifying a JAVA method to invoke for
retrieving this method; and
in the case of said loaded JAVA class implementing said predefined interface
iteratively processing each field descriptor within the loaded JAVA class to retrieve
corresponding XML tag; and
15 transferring field values to new elements created using said corresponding XML
tags.
2. A method for processing an XML document to produce a JAVA class, comprising:
instantiating an object of the desired JAVA class;
20 in the case of said instantiated object, implementing a predefined interface,
iteratively processing each object included within said instantiated object according to the
steps of:
retrieving field descriptors associated with an object being processed;
creating an object of specified JAVA type for each XML element corresponding to
25 a field descriptor; and
storing the created object in the currently processed object.
3. A method for adapting a JAVA object to an application programming interface
(API) for converting said JAVA object to eXtensible Markup Language (XML),
30 comprising:

T06TH06262E860

annotating said JAVA object to include, for each JAVA object to be converted to XML, identification of a respective XML tag, identification of a JAVA class to be instantiated when constructing said JAVA object field from an XML file, identification of a JAVA method to invoke for retrieving said JAVA object and identification of a JAVA method to invoke for retrieving said retrieval method.

4. An application programming interface (API) for converting at least from JAVA to extensible mark-up language (XML), comprising:

a field description retrieval method, for determining JAVA conversion parameters by examining an annotation associated with each JAVA element to be converted to XML, said annotation defining for each JAVA element at least a corresponding XML tag, a corresponding object class, a corresponding field retrieval method, and a corresponding method retrieval method.

5. The API of claim 4, further comprising:

a JAVaToXML conversion method implemented according to the steps of:
loading the named JAVA class;

determining if the loaded JAVA class implements a predefined interface, said predefined interface comprising annotations including a first parameter, for associating said JAVA class field with a corresponding XML element tag, a second parameter, for specifying a JAVA class to be instantiated when constructing said JAVA class field from said XML file, a third parameter, for identifying a JAVA method to invoke for retrieving said JAVA class field, and a fourth parameter, for identifying a JAVA method to invoke for retrieving this method; and

in the case of said loaded JAVA class implementing said predefined interface iteratively processing each field descriptor within the loaded JAVA class to retrieve corresponding XML tag; and

transferring field values to new elements created using said corresponding XML tags.

6. The API of claim 4, further comprising:
an XMLtoJAVA conversion method, comprising:
instantiating an object of the desired JAVA class;
in the case of said instantiated object implementing a predefined interface,
5 iteratively processing each object included within said instantiated object according to the steps of:
retrieving field descriptors associated with an object being processed;
creating an object of specified JAVA type for each XML element corresponding to
a field descriptor; and
10 storing the created object in the currently processed object.
7. A data structure for describing a JAVA class field in a manner facilitating XML conversion, comprising:
a first parameter, for associating said JAVA class field with a corresponding XML
15 element tag;
a second parameter, for specifying a JAVA class to be instantiated when constructing said JAVA class field from said XML file;
a third parameter, for identifying a JAVA method to invoke for retrieving said
JAVA class field; and
20 a fourth parameter, for identifying a JAVA method to invoke for retrieving this method.
8. The data structure of claim 7, further comprising:
a fifth parameter, for specifying a type of JAVA object to instantiate for an XML
25 element representing a collection.
9. The data structure of claim 8, further comprising:
a sixth parameter, for specifying a tag name to use for each element representing a
collection.

10. The data structure of claim 8, wherein said collection comprises a HashTable.
-

slat

09837929-041901
T06T40" 626ZE850